



Circuit Diagram

P.C.B.Land Pattern

主要技术参数、性能
The Main Thchnology Performance

额定电流、电压 Rate voltage current	See detail spec
接触电阻 Contact resistance	50mΩ Max
绝缘电阻 insulated resistance	100mΩ Min
电寿命 Electrical Life	10,000 Cycles (Min)
使用温度 Service temperature	-25°C+ 80 °C
使用湿度 Ambient humidity used	≤85%RH
机械寿命 Mechanical Life	10,000 Cycles (Min)
耐焊温度 Withstand Soldering temperature	260°C ± 5°C 3S

E				
D				
C				
B				
A				
项目 ITEM	名称 DESCRIPTION	材质 MATERIAL	数量 QYT	表面处理/颜色 FINSH/COLOR

						第一视角 FIRST VIEW		名称/NAME: 拨动开关 TOGGLE SWITCH SERIES	
								型号/MODEL: K3-1270	
标记 SING	处数 FREQUENCY	更改文件号 REVISION	签名 APPROVED	日期 DATE	比列 SCALE	一般公差 GENERAL TOLERANCE			
设计 DESIGN		Zhaoming			单位 UNIT	mm	0.5~2	±0.10	
审核 CHECKED		Zengyong			重量 WELGHT		2~5	±0.15	
批准 APPROVED		Fuyunfeng					5~10	±0.20	
							角度 ANGLE	±0.5°	