


TIMING: NS
OPTIONAL KNOB TYPE
M 7-16 IG 5-10
G 1.5-15 WGA 0-15



主要技术参数、性能

The Main Thchnology Performance

| | |
|---|---------------------|
| 额定电流、电压 Rate voltage current | See detail spec |
| 接触电阻 Contact resistance | 50mΩ Max |
| 绝缘电阻 insulated resistance | 100mΩ Min |
| 电寿命 Electrical Life | 10,000 Cycles (Min) |
| 使用温度 Service temperature | -25°C+ 80 °C |
| 使用湿度 Ambient humidity used | ≤85%RH |
| 机械寿命 Mechanical Life | 10,000 Cycles (Min) |
| 耐焊温度 Withstand Soldering temperature | 260°C ± 5°C 3S |

| E | | | | |
|------------|-------------------|----------------|-----------|------------------------|
| D | | | | |
| C | | | | |
| B | | | | |
| A | | | | |
| 项目 ITEM | 名称 DESCRIPTION | 材质 MATERIAL | 数量 QYT | 表面处理/颜色 FINSH/COLOR |

| | | | | | | | | | |
|-------------|-----------------|-------------------|----------------|------------|--------------------|---------------------------|-------------|--|--|
| | | | | | 第一视角 FIRST VIEW | | | 名称/NAME: 拨动开关 TOGGLE SWITCH SERIES | |
| | | | | | | | | 型号/MODEL: SS-12F14(1P2T) | |
| 标记 SING | 处数 FREQUENCY | 更改文件号 REVISION | 签名 APPROVED | 日期 DATE | 比列 SCALE | 一般公差 GENERAL TOLERANCE | | | |
| 设计 DESIGN | | Zhaoming | | | 单位 UNIT | mm | 0.5~2 ±0.10 | | |
| 审核 CHECKED | | Zengyong | | | 重量 WELGHT | | 2~5 ±0.15 | | |
| 批准 APPROVED | | Fuyunfeng | | | | | 5~10 ±0.20 | | |
| | | | | | | | 角度 ANGLE | ±0.5° | |

