


主要技术参数、性能  
The Main Thchnology Performance

额定电流、电压 Rate voltage current	1mA 5VDC ~50 $\mu$ A 3V DC
接触电阻 Contact resistance	2 $\Omega$ ~5 $\Omega$ . MAX
绝缘电阻 insulated resistance	100m $\Omega$ Min 100V DC
使用湿度 Ambient humidity used	$\leq$ 85%RH
使用温度 Operating temperature	-25 $^{\circ}$ C+80 $^{\circ}$ C
耐焊温度 Withstand Soldering temperature	245 $^{\circ}$ C $\pm$ 5 $^{\circ}$ C 3S $\pm$ 0.5S
寿命 Life	50.000Cycles

E				
D				
C				
B				
A				
项目 ITEM	名称 DESCRIPTION	材质 MATERIAL	数量 QYT	表面处理/颜色 FINSH/COLOR

						第一视角 FIRST VIEW		名称/NAME: 检测开关 DETECTOR SWITCH	
								型号/MODEL: DS-3030B	
标记 SING	处数 FREQUENCY	更改文件号 REVISION	签名 APPROVED	日期 DATE	比列 SCALE	一般公差 GENERAL TOLERANCE			
设计 DESIGN		Zhaoming			单位 UNIT	mm	0.5~2	$\pm$ 0.10	 三荣部品
审核 CHECKED		Zengyong			重量 WELGHT		2~5	$\pm$ 0.15	
批准 APPROVED		Fuyunfeng					5~10	$\pm$ 0.20	
							角度 ANGLE	$\pm$ 0.5 $^{\circ}$	