



CIRCUIT DIAGRAM



Recommended PAD Layout $\Phi \pm 0.05$
 Recommended solder thickness $T = 0.10 \pm 0.01$

1. RATING: DC 12V, 20mA Max
2. OPERATING FORCE: 160 ± 40 gf
3. TRAVEL: 0.15 ± 0.05 mm
4. LIFE: 200,000 cycles
5. PACKAGE: 4500Pcs/Reel

8	BUTTON	1	LCP	BLACK	东莞市三荣部品电子有限公司 TOLERANCES UNLESS OTHERWISE SPECIFIED CLASS: <input type="checkbox"/> CONFIDENTIAL <input type="checkbox"/> SECRET <input checked="" type="checkbox"/> GENERAL WITHIN: 1.5mm±0.1mm OVER: 1.5mm±0.2mm NAME: TACT SWITCH APPD: PART NO. TS-2040 CHKD: FU XIAO FENG DR: ZENG YONG			
7	PLATED	1	PHOSPHOR BRONZE	Ag-Plate				
6	SHELL	1	PHOSPHOR BRONZE	Ag-Plate				
5	COVER	1	LCP	BLACK				
4	FILM	1	PI	YELLOW				
3	CONTACT	3	SUS	Ag-Plate	UNIT	SCALE	SHEET	UNIT
2	TERMINAL	2	PHOSPHOR BRONZE	Ag-Plate	mm	1:1	1/1	B
1	HOUSING	1	LCP	BLACK				
ITEM	PART NAME	Q'TY	MATERIAL	FINISH				